
LED Driver Constant voltage





IP20 independant LED convertor, for indoor use. With output of DC 12V OR DC24V,Max.15W. Class ${\rm II}$ protection against electric shock following direct and indirect contact.

Protections:

- -against overheating and short circuits.
- -against open circuits.
- -againdt overloads.

Auto restart after fault condition removal.

Comply with IEC EMC and safety requirement.

Input Voltage: 220-240V AC 50/60Hz




■ LC15-12VF/LC15-24VF

Code	Model	W	I out	V out	Ta° C	Tc° C	L×W×H(mm)	Weight(g)
io-602005	LC15-12VF	0.5-15W	1.25A	12V	45	75	118×43×22	85
io-602006	LC15-24VF	0.5-15W	0.63A	24V	45	75	118×43×22	85

S)(€



LED Driver Constant voltage



IP20 independant LED convertor, for indoor use. DC 12V or DC 24V constant coltage output, Max.30W. Class

☐ protection against electric shock following direct and indirect contact.

High power factor[≥0.95].

Protections:

- -against overheating and short circuits.
- -against open circuits.
- -againdt overloads.

Auto restart after fault condition removal.

Comply with IEC EMC and safety requirement.

Input Voltage: 220-240V AC 50/60Hz

LC30-12VF/LC30-12VF

Code	Model	W	I out	V out	Power factor	Ta° C	Tc° C	L×W×H(mm)	Weight(g)
io-602007	LC30-12VF	3-30W	2.5A	12V	≥0.95	45	75	150×40×30	155
io-602008	LC30-24VF	3-30W	1.25A	24V	≥0.95	45	75	150×40×30	155